

RICOH SP 6430DN





Print larger sizes in smaller space with the RICOH SP 6430DN.

SP 64300

5

The RICOH SP 6430DN is a printer with solid fundamental performance and the reliability to keep your work rolling non-stop. The SP 6430DN uses LED printhead technology, allow high-quality of 1200 x 1200 resolution printing in black and white drawings, schematics, floor plans and more with sizes up to 11" x 17".

The RICOH SP 6430DN

RICOH SP 6430DN Key Features

Start printing quickly

The longer you have to wait for a print job, the less time you have to work on the next one. Meet deadlines without compromising quality with the small but powerful Ricoh SP 6430DN printer. Warm up time is less than 17 seconds, and first print time is only 6.5 seconds, so you can begin printing almost immediately. With output speeds up to 38 pages per minute, even at optimal resolution, you can finish your project and transition to the next job quickly.

Handle a wider range of jobs

Improve efficiency and productivity with the Ricoh SP 6430DN. Bring more projects in-house with expansive media handling options that allow you to print on ledger size paper, thicker stocks, letterhead, recycled paper, labels and even envelopes with crisp 1200 x 1200 resolution. Need CAD drawings, manufacturing designs, financial spreadsheets or real estate floor plans? Print at up to 11" x 17" so you and your customers can see exact details of the project with more clarity, which will help make those difficult design decisions easier and more convenient.





Cost efficiency and Environmental Compliance

Reduce paper and supply cost with default automatic duplex printing. With the ECO-Night Sensor, you can program the Automatic startup and shut down of the printer base on ambient light. This effectively conserve energy when the office is closed. In addition, the Ricoh SP 6430DN is ENERGY STAR certified and offers incredibly low typical electricity consumption (TEC).

Use a more secure network and protect data

You may share a printer with your coworkers, but you probably don't want to share everything. If you work in banking, human resources or other organization that manages confidential information, security is important. With the USB Device Server option, you can use a different IP address to connect the Ricoh SP 6430DN to a second secure network to safeguard specific information from the Internet and other security threats. In addition, with an optional Hard Disk Drive you can use Locked Print function to hold jobs at the printer until the user authenticate to release it. This ensure confidentiality.





SYSTEM SPECIFICATIONS

ENGINE SPECIFICATIONS		CONTROLLER SPECIFICATIONS		CONTROLLER OPTION
SP 6430DN		Processor Speed	533 MHz	-USB Device Server Option
Configuration	Desktop	Memory	512MB/ 1 GB RAM	-250 GB Hard Disk Drive
Technology	LED	(Standard/Maximum)		-1.0 GB Memory Unit
Printing Process	Electro-photographic	Hard Disk Drive	250 GB (Optional)	-IEEE 802.11 Interface Unit
	printing	Connection Type	10/100/1000Base-TX Ethernet	-IEEE 1284 Interface Board
Toner Type	Dry, single component		(RJ45)	-VM Card
Control Panel	4-line LCD		Gigabit Network Interface	-XPS Direct Print Option
Print Resolution	300 x 300 dpi/600 x 600dpi/		USB 2.0 High Speed Type B	
	1200 x1200 dpi		(for direct computer	
B&W Print Speed (A4)	38 Pages per minute		connection)	HARDWARE OPTIONS
Maximum Monthly	20,000 prints		Dual USB 2.0 Host Type A	-Paper Feed Unit TK2010
Volume			(for external device connection)	500 Sheets Paper Capacity
Maximum Monthly	150,000 prints		Dual SD Card Slots	Dimension (W x D x H)
Duty Cycle			(for expanded functions/device	(459 mm x 392 mm x 124 mm)
First Page Output	6.5 seconds or less		customization)	Weight (6 kg)
Warm-Up Time	17 seconds or less	Optional Interfaces	USB Device Server	
Standard Paper Capacity		Optional interfaces		
standard Paper Capacity	600 sheets (500-sheet Tray		IEEE 802.11a/b/g/n Wireless LAN	CONSUMABLE AND YIELDS
Maximum Paper	+ 100-sheet Bypass Tray) 2.100 sheets		Type O	Print Cartridge Approx 10,000
•	2,100 sheets		IEEE 1284/ECP Parallel Interface	5
Capacity Standard Output			Type A	Pages* Drum Unit Approx 25,000
Standard Output	Up to 500 sheets, face	Printer Languages	PCL6/5e	FF
Capacity	down		Adobe PostScript 3	Pages Maintenance Kit Approx 90,000
Supported Paper Sizes	Standard Tray :		PDF Direct Print	
	A3,A4,A5,B4, B5,B6,		Optional : IPDS*, XPS	Pages
	Letter Size, Legal size	Font Support	PCL5:45 fonts + 13 International	*Declared yield values in accordance with
	Optional Tray :		fonts	ISO/IEC 19752
	A3,A4,A5,B4, B5,B6,		PCL6:45 fonts	Actual yields may vary based on types of
	Letter Size, Legal size		Postscript 3 :136 fonts	images printed and other factors
	Bypass Tray :		IPDS: 1008 fonts (optional)	inages printed and other factors
	A3,A4,A5,B4, B5,B6,	Network Protocols	TCP/IP	The Ricoh SP 6430DN ships with starter tone
	Letter Size, Legal size	Supported Operating	Windows XP/Vista/7/8/8.1/	that yields 6,000 pages (ISO/IEC 19752)
Supported Paper	All Trays : 56 – 220 gsm	Systems	Server2003/Server2008/	, , , ,
Weights	Duplex (56 – 162gsm)		Server2008 R2/Server2012/	For Maximum performance and yield, we
Supported Paper Types	Plain paper, Thick paper,		Server2012 R2	recommend using genuine Ricoh parts and
	Recycled paper, Special		Mac OS (X10.6 or later) *PS	supplies.
	paper, Color paper,		only	Specifications subject to change without
	Letterhead, Preprinted,		Web Image Monitor, @Remote,	notice
	Label paper, Envelop	Device Management	Device Manager NX series,	
Duplexing	Automatic (Standard)	Utilities	Printer Driver Packager NX	
Dimensions (WxDxH)	459 mm x 392 mm x	Mobile Print	Ricoh Smart Device Print&Scan	
	347.5 mm		Арр	
Weight	22.5Kg	Other Print Features	Reduce/Enlarge, Collate,	
Power Consumption	1,073w or less		Layout(N-up),Toner Saving,	
(Operating)			Watermark, Rotate Print,	
Power Consumption	0.57W or less		Support for Universal Driver,	
(Sleep Mode)			Sample Print, Hold Print, Store	
Typical Electricity	2.31kwh or less		and Print, Media Direct	
Consumption (TEC)	2.510011035		Print(print from USB/SD),Banner	
Power Requirements	220 – 240V, 50/60Hz		Page Print, Poster Print, Wi-Fi	
Recovery from Sleep	5.0 seconds or less		Protected Support	
Mode			(WPS),External USB Keyboard	
	Cortified		Support, Import/Export of	
Energy Star EPEAT	Certified Gold		Preference Settings.	
	GOIG		reference settings.	

RICOH imagine. change.

www.ricoh-ap.com

RICOH ASIA PACIFIC PTE LTD

103 Penang Road #08-01/07, VISIONCREST Commercial, Singapore 238467 Phone: +65 6830 5888, Fax: +65 6830 5830

All brand and/or product names are trademarks of their respective owners. Specifications and external appearance are subject to change without notice. The colour of the actual product may vary from the colour shown in the brochure. The images in this brochure are not real photographs and slight differences in detail might appear. Copyright © 2014 Ricoh Asia Pacific Pte Ltd. All rights reserved. This brochure, its contents and/or layout may not be modified and/or adapted, copied in part or in whole and/or incorporated into other works without the prior written permission of Ricoh Asia Pacific Pte Ltd.